

IN114xv

InFocus

Unsurpassed lamp life. Unbeatable value.

Part #: IN114xv

This model is sold out in the Americas. Review our [current projector line-up](#).

The IN114xv projector is an incredible value with ultra-long lamp life, high brightness, and outstanding image quality. This value-packed projector is easy to buy and built to perform with HDMI input, high contrast, and BrilliantColor™ technology. Plus, the compact design and light weight makes it as easy to move around as it is to install.

EMEA and Asia-Pacific Regions

Key Features

- ◆ XGA (1024 x 768) resolution
- ◆ 3800 lumens
- ◆ Long 15,000 hour lamp life
- ◆ High 26000:1 contrast ratio
- ◆ Compact and light weight for easy portability
- ◆ Accurate and vivid color reproduction with BrilliantColor™ technology
- ◆ HDMI connectivity
- ◆ Display 3D content from Blu-ray and PCs



High Brightness and High Contrast

Get better, brighter images on any surface, in any light. The IN110xv series has up to 3800 lumens and a 26,000:1 contrast ratio for whiter whites, darker blacks, and overall image sharpness. Preset modes give you great image quality on beige walls, whiteboards, or blackboards.

Industry-leading Lamp Life

The IN110xv Series features up to an unprecedented 15,000 hours of lamp life when used in Dynamic Mode. With no filters to replace, these projectors are an unbeatable value.

3D Ready

The IN110xv Series supports multiple forms of 3D – including Blu-Ray, 3D broadcasting, video games and PC connectivity. All your audience needs are [144Hz DLP Link 3D glasses](#) (sold separately) to seamlessly synchronize with the image for an awesome 3D experience.

Advanced Presentation and Setup Features

Equipped with AV Mute, test patterns, image shift and other advanced features, the IN110xv Series delivers your content powerfully without complicated set-up.

Specifications*

Projector		IN114xv
Resolution – Native		XGA (1024 x 768)
Resolution – Maximum		WUXGA (1920 x 1200)
Display Technology		DLP
Video Standard Compatibility		NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 720p, 1080i, 1080p
Lamp Brightness		3,800 lumens
Lamp Brightness – Low Power		2,700 lumens
Lamp Life		6,000 hours
Lamp Life – Low Power		7,200 hours
Lamp Life – Dynamic Mode		15,000 hours
Lamp Power		195W
Lamp Power – Low Power		160W
Lamp Power – Dynamic Mode		60W
Replacement Lamp		SP-LAMP-097
Contrast Ratio		26,000:1
Color Wheel		6 segment, 2x speed
Number of Colors		1.07 billion
Synch Scan Frequency – Horizontal		31.469kHz ~ 97.551kHz KHz
Synch Scan Frequency – Vertical		56 - 85 Hz (120Hz for 3D feature projector) KHz
Aspect Ratio		4:3
Aspect Ratio Compatibility		16:9, 16:10
Projection Distance – Minimum		1 m
Projection Distance – Maximum		12 m
Lens Type		Manual zoom and focus
Image Size – Minimum		28 in
Image Size – Maximum		300 in
Projection Offset		15%
Keystone Correction		± 40°V
Connectors – Inputs		Composite video, S-video, VGA, HDMI 1.4b
Control		Projector Keypad, IR Remote, USB-B for presentation control
Audible Noise		< 31 dBA at 0°F / -17.8°C
Audible Noise – Eco Mode		< 28 dBA at 0°F / -17.8°C
Included Accessories		Power cord, Remote, VGA cable, Documentation
3D Support		1080p @ 60 Hz via HDMI, DLP Link 3D glasses required
Product Warranty		2 years
Lamp Warranty		6 months
Accessories Warranty		90 days
Computer Compatibility		PC, Mac
Operating Conditions		32 to 73.4°F at 0 to 10000 ft / 0 to 23°C at 0 to 3048 m
Menu Languages		English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Polish, Turkish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai
Approvals		UL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, CB, Nemco/GS, KC
Throw and Zoom		
Throw Ratio – Minimum		1.95:1
Throw Ratio – Maximum		2.15:1
Zoom Ratio		1.1:1
Shipping		
Product Dimensions		4 x 12.4 x 8.8 in / 101.6 x 315 x 223.5 mm
Product Weight		5.5 lbs / 2.5 kg
Shipping Dimensions		7.8 x 14.3 x 12 in / 198.1 x 363.2 x 304.8 mm
Shipping Weight		7.3 lbs / 3.3 kg
UPC		797212987587

Accessories

Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
Motorized Electric Projector Screen: 120 in., 4:3 (SC-MOT-120)
Projector Lamp for the IN110xa and IN110xv Series (SP-LAMP-097)
LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)
Soft Carry Case for Office/Classroom Projector (CA-SOFTCASE-MTG)
Soft Carry Case for Value Projectors (CA-SOFTVAL-2)
Replacement Remote for Select InFocus Projectors (INA-REMPJ001)
Replacement Remote for Select InFocus Projectors (INA-REMPJ001a)
Projector Ceiling Mount System (White) (PRJ-MNTKIT-UNIVW)
Projector Ceiling Mount System (Black) (PRJ-MNTKIT-UNIVB)
LiteShow Mount Adapter (PRJ-MNT-LS3)
Manual Pull Down Projector Screen: 84 in., 4:3 (SC-MAN-84)
Manual Pull Down Projector Screen: 100 in., 4:3 (SC-MAN-100)
Manual Pull Down Projector Screen: 120 in., 4:3 (SC-MAN-120)
Fixed Frame Projector Screen: 84 in., 4:3 (SC-FF-84)
Fixed Frame Projector Screen: 100 in., 4:3 (SC-FF-100)
Fixed Frame Projector Screen: 120 in., 4:3 (SC-FF-120)
Motorized Electric Projector Screen: 84 in., 4:3 (SC-MOT-84)
Motorized Electric Projector Screen: 100 in., 4:3 (SC-MOT-100)
Manual Pull Up Projector Screen: 80 in., 4:3 (SC-PU-80)
Manual Pull Up Projector Screen: 100 in., 4:3 (SC-PU-100)
1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1)
2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)